

MultiWeigh MW XV-Triple Highspeed for Sweets and Fruitgums



| Type | Weighing range | Max.Volume/ Discharge | Performance |
|-----------------------|----------------|--------------------------|-------------|
| MW XV 18-1.0-Triple | 2g to 50g | 250 ccm | 180/min |
| MW XV 18-1.0-M-Triple | 2g to 500g | 750 ccm | 210/min |

Precision, reliability, hygiene, high performance

- ▶ High capacity and accuracy
- ▶ Low cleaning intervals
- ▶ Product contacting parts quick releasable
- ▶ Maintenance free
- ▶ Modular design
- ▶ Compliance with ingress protection IP67 and higher
- ▶ Special executions for sticky products, fragile products, granulated products



MultiWeigh® "Direct-Drive System",
steppermotor operated hoppergates

- ▶ PTB Approval, compliance with OIML R 61
- ▶ Precise, fast hoppergate motion
- ▶ Maintenance free, without pullback springs
- ▶ Low noise pollution
- ▶ Multiweigh® "Hopper Control" recognizes and displays malfunctions
- ▶ Hoppers fully interchangeable

Sophisticated control technology



- ▶ Multiweigh® Touchscreen Control Unit
- ▶ Multiweigh® -PC-Control multiprocessortechology
- ▶ Modular electronic units placed in the actuator modules
- ▶ Easy programmable, interactive software
- ▶ 200 program setups
- ▶ Multilingual
- ▶ Self-diagnosis with failure report
- ▶ Network communication ports
- ▶ Remote maintenance via VPN
- ▶ Statistic and production data protocol
- ▶ Automatic optimising of production speed
- ▶ Automatic optimising of average weight
- ▶ Automatic taring
- ▶ Calibration prog