



MultiWeigh®

Precision in weighing technology

MultiWeigh MW XV-W

MultiWeigh technology down-the-line:
universally applicable



Type	Weighing range	Max.Volume/ Discharge	Performance
MW XV 10-2.0	30g to 2.500g	5.000 ccm	70/min
MW XV 10-4.0	30g to 5.000g	10.000 ccm	60/min
MW XV 10-6.0	30g to 5.000g	15.000 ccm	60/min
MW XV 10-8.0	30g to 5.000g	15.000 ccm	70/min
MW XV 14-2.0	30g to 2.500g	5.000 ccm	120/min
MW XV 14-4.0/6.0	30g to 2.500g	10.000 ccm	110/min
MW XV 14-5.0/7.0	30g to 2.500g	12.000 ccm	100/min
MW XV 16-2.0	30g to 2.500g	5.000 ccm	140/min
MW XV 16-4.0	30g to 2.500g	10.000 ccm	130/min
MW XV 18-2.0	30g to 2.500g	5.000 ccm	140/min
MW XV 20-2.0	30g to 2.500g	5.000 ccm	140/min
MW XV 20-4.0	30g to 2.500g	5.000 ccm	130/min
MW XV 24-2.0	30g to 2.500g	5.000 ccm	140/min



Precision, reliability, hygiene, high performance

- ▶ High capacity and accuracy
- ▶ Low cleaning intervals
- ▶ Product contacting parts quick releasable
- ▶ Maintenance free
- ▶ Modular design
- ▶ Compliance with ingress protection IP67 and higher
- ▶ Special executions for sticky products, fragile products, granulated products



MultiWeigh® "Direct-Drive System",
steppermotor operated hoppergates

- ▶ PTB Approval, compliance with OIML R 61
- ▶ Precise, fast hoppergate motion
- ▶ Maintenance free, without pullback springs
- ▶ Low noise pollution
- ▶ Multiweigh® "Hopper Control" recognizes and displays malfunctions
- ▶ Hoppers fully interchangeable

Sophisticated control technology



- ▶ Multiweigh® Touchscreen Control Unit
- ▶ Multiweigh® -PC-Control multiprocessortechnology
- ▶ Modular electronic units placed in the actuator modules
- ▶ Easy programmable, interactive software
- ▶ 200 program setups
- ▶ Multilingual
- ▶ Self-diagnosis with failure report
- ▶ Network communication ports
- ▶ Remote maintenance via VPN
- ▶ Statistic and production data protocol
- ▶ Automatic optimising of production speed
- ▶ Automatic optimising of average weight
- ▶ Automatic taring
- ▶ Calibration prog